

DECLARATION OF PERFORMANCE
SUPERCEL® FLAMMA
N. CPR-FM/24.0






1. Unique identification code of the product-type: **SUPERCEL® FLAMMA**
2. Intended use/es: **Thermal insulation for buildings - Factory made phenolic foam (PF)**
3. Manufacturer: **Resine Isolanti O. Diena S.r.l. - Viale Zanotti, 86 - 27027 Gropello Cairoli (PV)**
4. System of assessment and verification of constancy of performances: **AVCP - System 3**
5. Harmonized technical specification: **EN 13166:2012+A2:2016**
6. Notified bodies:
No. 0497 - CSI S.p.a. Viale Lomabardia, 20 - 20021 Bollate (MI)
No. 0407 - Istituto Giordano S.p.a. Via Gioacchino Rossini, 2 - 47814 Bellaria - Igea Marina (RN)
7. Declared characteristics:

Essential characteristics		Performances
Thermal resistance	Thermal resistance R_D [(m ² .K)/W]	d _N 20mm 0,95
		d _N 30mm 1,40
		d _N 40mm 1,90
		d _N 50mm 2,35
d _N 60mm 2,85		
d _N 70mm 3,30		
d _N 80mm 4,20		
d _N 90mm 4,70		
d _N 100mm 5,25		
d _N 110mm 5,75		
d _N 120mm 6,30		
d _N 130mm 6,80		
d _N 140mm 7,35		
d _N 150mm 7,85		
d _N 160mm 8,40		
	Thermal conductivity λ_D [W/(m.K)]	d _N 20mm-79mm 0,021 d _N 80mm-160mm 0,019
	Thickness	d _N 20mm-160mm T1
	Closed cell content	CV
Reaction to fire	Euroclass	B-s₁,d₀
Durability of reaction to fire against heat, weathering, aging / degradation		
Dimensional stability under specified temperature and humidity condition	Pass	DS(70,90) DS(-20,-)
Compressive strength	Compressive stress or compressive strength	CS(Y)120
Tensile / flexural strength	Tensile strength perpendicular to faces	NPD
Durability of compressive strength against aging / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	WS3
	Long term water absorption	NPD
Water vapor permeability	Water vapor transmission	NPD
Release of dangerous substances to the indoor environment		NPD
Continuous glowing combustion		NPD

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) n. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:
 Marco Diena, C.E.O.
 Milan, 30/08/2024


 RESINE ISOLANTI O. DIENA S.r.l.

 24 0497, 0407		 Resine Isolanti O.Diena Srl Viale Zanotti, 86 - 27027 Gropello Cairoli (PV) www.resineisolanti.com	
CPR-FM/24.0 EN 13166:2012+A2:2016 SUPERCEL® FLAMMA Thermal insulation for buildings - Factory made phenolic foam (PF) PF - EN 13166 - T1 - DS(70,90) - DS(-20,-) - CS(10/Y)120 - WS3 - TR80 - CV			
THERMAL CONDUCTIVITY	λ_D [W/(m.K)]	d _N 20mm-79mm	0,021
		d _N 80mm-160mm	0,019
THERMAL RESISTANCE	R _D [(m².K)/W]	Depending on thickness	
REACTION TO FIRE	EUROCLASS	B-s₁,d₀	
DURABILITY OF REACTION TO FIRE AGAINST HEAT; WEATHERING; AGING / DEGRADATION			
WATER PERMEABILITY	CLASS	WS3	
COMPRESSIVE STRENGTH	kPa	≥ 120	
TENSILE / FLEXURAL STRENGTH	kPa	NPD	
DIMENSIONAL STABILITY UNDER SPECIFIC TEMPERATURE AND HUMIDITY CONDITIONS	Passa	DS(70,90) DS(-20,-)	
WATER VAPOR PERMEABILITY	NPD		
RELEASE OF DANGEROUS SUBSTANCES	NPD		
DURABILITY OF COMPRESSIVE STRENGTH AGAINST AGING / DEGRADATION	Compressive creep	NPD	

REACH information:

This product is considered an article under Art.3 of the REACH Regulation (EC) N.1907/2006. Consequently, according to Art.31 and 33 of the same Regulation, it does not require a Safety Data Sheet. During use, it is recommended to refer to the indications given in the Technical Data Sheet and the safety regulations established in the workplace.

Additional information:

Resine Isolanti provides this designation code together with the DoP to facilitate the consultation of the CE marking by international customers. The marking shown here may differ from that indicated on the packaging or accompanying documents due to:

- declared NPD (No Performance Determined) values which can be omitted in the CE marking,
- graphic adaptations in relation to the available space and the printing media used,
- use of a different language (the same packaging is used in numerous countries),
- product already in stock at the time of updating the marking,
- printing errors.